

TYPICAL CHARACTERISTICS:

Appearance	Clear colorless fluid
Physical State	Liquid
Flash Point	> 100°C (212°F)
Decomposition Temperature	42.7°C (109°F)
Boiling Point	98°C (210°F)
Freezing Point	0°C (32°F)
Concentrate Specific Gravity	1.01 – 1.04
pH	10 – 11.5
Concentrate Density	8.42 – 8.67 lb/gal
Water Solubility	100%
Odor	No added odor

SDS AVAILABLE ONLINE

TYPICAL USES: Powerful, biodegradable cleaner and degreaser specially formulated to safely and effectively remove oil, grease and grime build-up which can harm expensive equipment and slow down rig operations.
See label for additional uses.

SAFETY: Use protective glasses or safety goggles if splashing or spray-back is likely. Use in well-ventilated areas or with local exhaust ventilation when cleaning small spaces. Use protective gloves (any material) when used for prolonged periods or if dermally sensitive.

SIMPLE GREEN® RIG WASH

Heavy-duty concentrate removes grease, oil and drill muds without harsh solvents

UNIQUE FEATURES

- Concentrated formula provides economical dilution ratios for both manual and pressure washing use
- Cleans without the harsh solvents found in other commonly used products, providing a safer alternative for employees, equipment and the environment
- Easily cuts through the heavy oils, grease and drill muds found in the petroleum industry, helping to keep equipment and vehicles running at optimum levels
- Biodegradable formula allows grease and oil to break back out of the solution, making it ideal for entry into oil/water separators and clarifier equipment
- Free of colors and dyes that may cause damage to equipment
- Non-flammable, non-abrasive formula
- Non-corrosive to metals

APPLICATIONS

- Ideal for cleaning on and off-shore drilling rigs and equipment
- Cleans and maintains platforms, decks, derricks, liners, casings, crown and traveling blocks, and blowout preventers
- Safe for metal and plastic piping as well as steel wire and cable, coiled tubing units, racks, trays and ramps
- Great on drills, bits and rods
- Cleans built-up residue from PC pumps, ESP pumps, pump jacks, and pump pads
- Versatile formula is also ideal for equipment and vehicles such as frac blenders, cranes, trucks, trailers, auxiliary vehicles, engines, and generators

DIRECTIONS FOR USE

Spot test on an inconspicuous area first. If using above eye-level or if spray could contact eyes, wear eye protections.

1. Mix with water per application type.
2. Apply to soiled surfaces manually or with a pressure washer.
3. Allow time for the solution to penetrate the soils (but not dry).
4. Agitate heavily soiled areas.
5. Rinse with water at highest available pressure.

NOTE: Do not allow contact with asphalt.



PART#	SIZE	UNITS	CASE WEIGHT	CASE DIMENSIONS	UPC
0110000403001	1 US gal	4	37.00 lb	13.00 x 13.00 x 12.50	0-43318-00234-9
0100000103005	5 US gal	1	46.00 lb	N/A	0-43318-00235-9
0100000103055	55 US gal	1	495.00 lb	N/A	0-43318-00244-1
0100000103275	275 US gal	1	2484.00 lb	N/A	0-43318-00264-9